




Technical Product Specifications: ***CABLE TRAY***

Approval/calculation possibilities:

- NZS1170.5:2009
- NZS 4219:2009
- AS/NZS 4680:2006





FDG CABLE TRAY

FDG Cable Tray is designed to continuously support cable systems including; Power, Data, and Audio Visual. A quick and easy system to install without the need for specialised tools or equipment, makes it a first choice for Commercial and Industrial electricians.

Available in a range of cable laying depths and widths, we have a solution that works for your job. This tray is stocked in a range of Pre-Galv and Hot Dip Galv finishes, which can also be powder coated and panted in a wide range of colours on request.

The FDG Tray System can be easily modified and adapted to accommodate changes in cable configurations, making it a highly versatile solution for projects of all sizes. It also allows for easy access to cables, which simplifies future maintenance and repair work.




Advantages of using FDG CABLE TRAY

- Easy to install with no specialised tools required.
 - Modular System.
 - Powder Coating and Painting of Cable Tray available on request.
 - Wide Range of sizes and support capacities available.
 - Adjustable and configurable to suit your project.
-


Contents

4




CT3 CABLE TRAY
Heavy Duty

5




CT3 ACCESSORIES
Heavy Duty

6



CT5 CABLE TRAY
Heavy Duty

7




CT5 ACCESSORIES
Heavy Duty


FDG CT3 Cable Tray

Heavy Duty

- **Safety Factor:** 1.5
- **Finish:** Pre-Galv (Z275) and Hot Dip Galv (HDG)
- **Material:** Thickness: 0.8 mm



CT3 Cable Tray - Heavy Duty							
Code	Cable Laying Width mm "W1"	Overall Width mm "W2"	Cable Laying Depth mm	Length mm	Overall Height mm	Weight Pre-Galv	Weight Hot Dip Galv
FDG-CT3150	150	172	45	3000	50	5.3 kg	5.7 kg
FDG-CT3300	300	322	45	3000	50	7.8 kg	8.1 kg
FDG-CT3450	450	472	45	3000	50	10.1 kg	10.6 kg
FDG-CT3600	600	622	45	3000	50	12.6 kg	13.1 kg




*FDG-CT3 has been tested in accordance with the NEMA requirements. The data displayed is based on physical test results of a 600 wide section and may vary for other widths. The Deflections have been provided as a guide based on continuous spans, and cannot be applied to end spans.


■ FDG CT3 Accessories

Heavy Duty


Side Hold Down Bracket




Riser Plate




Radius Plate




Splice Plate




T Bracket



Centre Hold Down Clamp





Splice Bolt and Nuts




FDG CT5 Cable Tray

Heavy Duty

- **Safety Factor:** 1.5
- **Finish:** Pre-Galv (Z275) and Hot Dip Galv (HDG)
- **Material:** Thickness: 0.8 mm



CT5 Cable Tray - Heavy Duty							
Code	Cable Laying Width mm "W1"	Overall Width mm "W2"	Cable Laying Depth mm	Length mm	Overall Height mm	Weight Pre-Galv	Weight Hot Dip Galv
FDG-CT5150	150	172	80	3000	85	5.7 kg	5.9 kg
FDG-CT5300	300	322	80	3000	85	8.3 kg	8.7 kg
FDG-CT5450	450	472	80	3000	85	10.3 kg	10.8 kg
FDG-CT5600	600	622	80	3000	85	13.3 kg	14.0 kg




*FDG-CT5 has been tested in accordance with the NEMA requirements. The data displayed is based on physical test results of a 600 wide section and may vary for other widths. The Deflections have been provided as a guide based on continuous spans, and cannot be applied to end spans.


FDG CT5 Accessories

Heavy Duty


Side Hold Down Bracket




Riser Plate




Radius Plate




Splice Plate




T Bracket



Centre Hold Down Clamp



Splice Bolt and Nuts





sales@fdgnz.com

20 Mansel Dr, Warkworth, Auckland 0910 New Zealand

09-275-6811

This document is issued by Fasteners Direct Global Limited ("FDG") for general technical guidance only, and is intended for suitably qualified engineers and construction professionals. Performance data is derived from technical information published by the product manufacturer.

The information applies only to the product configuration, installation conditions and standards current at the date of issue, and within the range and configurations stated. It is not a substitute for independent engineering judgement and must not be the sole basis for design, certification or construction decisions. Determining the product's suitability for a specific application, and compliance with all applicable codes and project requirements, remains the responsibility of the project engineer.

Nothing in this document constitutes a warranty or guarantee of performance in service. FDG may revise or withdraw it at any time and accepts no liability, to the maximum extent permitted by law, for any loss arising from reliance on it or on a superseded revision.