




Technical Product Specifications:

STRUT BRACKETRY

Approval/calculation possibilities:

- AS/NZS 4600:2018
- NZS 4100:2020
- NZS1170.5:2009
- NZS 4219:2009
- NZS 4541:2020
- AS/NZS 4680:2006





STRUT BRACKETRY

FDG stocks a wide range of Strut Channel Brackets, a crucial part of the modular nature of the FDG Channel System. The different brackets available allow you to create many different frames and assemblies to meet your support requirements. The Spring Nut fastening system creates a proven connection that gives strength and versatility to your build.


FDG Strut Brackets are critical for creating rigid seismic bracing assemblies. With a wide range of fixed and hinged brackets available this strong and easy to install bracing systems gives you the options you require. The FDG Strut Brackets are stocked standard as Hot Dip Galvanized, however are also available in ZP, Stainless Steel or painted finishes if required.

Advantages of using STRUT BRACKETRY


- Wide range of bracketry.
 - Multiple combinations for assembly.
 - Simple Spring Nut connection system.
 - Easy to Install.
 - Removes need for welding and drilling.
-




Contents




Spring Nut




Flat Plate




Flat Plate & 90° Angle




90° & 45° Angle




"Z", "U"




"U" & Wing Shape




Adjustable Brace Fittings



Base Plates



Beam Clamps



Cantilever Brackets


Spring Nut

- **Safety Factor:** 3
- **Finishes Available:** Zinc Plate, Hot Dip Galvanised, Stainless Steel SS316

[BACK TO CONTENTS](#)

Zinc Spring Nut			
Nut Type	Pullout	Slip (8.8 Bolts)	Torque
NUTM6SLSZ	2.70 kN	1.30 kN	9 Nm
NUTM8SLSZ	3.55 kN	2.20 kN	22 Nm
NUTM10SLSZ	4.45 kN	3.50 kN	44 Nm
NUTM12SLSZ	8.85 kN	6.50 kN	77 Nm


- Slip testing carried out in New Zealand using 8.8 Grade Zinc Bolts.
- Strut Bracketing Capacity usually limited by Slip Capacity of Spring Nut.




Flat Plate

- **Hole Diameter:** 14mm
- **Hole Spacing (From End):** 21mm
- **Hole Spacing:** 48mm
- **Width:** 40mm
- **Thickness:** 6mm
- **Finish:** Hot Dip Galvanised


Square Plate Washers	
Code	Hole Size
W8X40SQX6G	M8
W10X40SQX6G	M10
W12X40SQX6G	M12
W16X40SQX6G	M16



FDG1065G



FDG1066G




Flat Plate


- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm
- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[BACK TO CONTENTS](#)


FDG1067G




FDG1941G




FDG1873G




FDG1036G



FDG2324G



FDG2325G




■ Flat Plate & 90° Angle

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm


- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[!\[\]\(d3fb9f94af8b26d1c844efa9a98805b0_img.jpg\) BACK TO CONTENTS](#)


FDG1358G




FDG1031G




FDG1028G




FDG1026G



FDG1068G



FDG1326G




■ 90° Angle

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm


- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[!\[\]\(9dfdaff1d86ba3c1f8353b4d1b61b8c5_img.jpg\) BACK TO CONTENTS](#)


FDG1346G




FDG1458G




FDG1325G




FDG2484G



FDG1037G



FDG1038G




90° & 45° Angle

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm


- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[BACK TO CONTENTS](#)


FDG1033G




FDG1034G




FDG1035G




FDG1357G



FDG1359G



FDG1186G




45° Angle

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm


- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[BACK TO CONTENTS](#)


FDG1546G




FDG1546G-3H




FDG4045G



FDG1045G




FDG1736G



FDG2452G

Design Load - 5.4kN




■ "Z", "U"

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm


- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[!\[\]\(0f848bbd71cef6b345273b16f905912a_img.jpg\) BACK TO CONTENTS](#)


FDG5545G




FDG1453G




FDG4047G




FDG1047G



FDG5547G



FDG1737G




■ "U" & Wing Shape


- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm
- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[!\[\]\(4729e517bc6a7cd81c8025b9646574fb_img.jpg\) BACK TO CONTENTS](#)


FDG2223G




FDG1044G




FDG1046G




FDG4376G



FDG1376G



FDG1377G




Wing Shape


- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm
- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[BACK TO CONTENTS](#)


FDG2228G



FDG2224G




FDG2346G




Adjustable Brace Fittings

- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm
- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised


FDG1843G



FDG1354G



FDG1354AG





Base Plates



- Hole Diameter: 14mm
- Hole Spacing (From End): 21mm
- Hole Spacing: 48mm
- Width: 40mm
- Thickness: 6mm
- Finish: Hot Dip Galvanised

[BACK TO CONTENTS](#)


FDG2072SIG



FDG2072BG & FDG2072AG





FDG2072G




FDG2072AG

FDG2073BG & FDG2073AG



FDG2073G




FDG2073AG

Beam Clamps

[BACK TO CONTENTS](#)

FDG1386G


- **Design Load:** 2.5 kN (Using the FDG1000 channel)
- **Finish:** Hot Dip Galvanised



- M12 x 40 bolt and channel nut not included.
- Ensure these brackets are used in pairs.

FDG1379G

- **Design Load:** 2.5 kN (Using the FDG1000 channel)
- **Finish:** Hot Dip Galvanised



- M12 x 40 cone point screw included.
- Ensure these brackets are used in pairs.


FDG2785G & FDG2786G

FDG2785G (Works with FDG1000 & FDG3300)

- **Leg Length:** 86mm
- **Design Load:** 4.5 kN each
- **Finish:** Hot Dip Galvanised

FDG2786G (Works with FDG1001 & FDG5500)

- **Leg Length:** 127mm
- **Design Load:** 4.5 kN
- **Finish:** Hot Dip Galvanised




- Ensure these brackets are used in pairs.

Beam Clamps

[BACK TO CONTENTS](#)

FDG1796G


- **Design Load:** 2.5 kN (Using the FDG1000 channel)
- **Finish:** Hot Dip Galvanised



- M12 x 40 cone point screw included.
- Ensure these brackets are used in pairs.

FDG1272G


- **Design Load:** 2.0 kN
- **Finish:** Hot Dip Galvanised



- M12 x 40 cone point screw included.
- Ensure these brackets are used in pairs.

FDG3087G

- **Design Pull-out Load:** 4.5 kN (Using FDG1000)
- **Design Slip Load:** 3.5 kN (Using FDG1000)
- **Finish:** Hot Dip Galvanised




- Ensure these brackets are used in pairs.
- M12 x 40 cone point screw included.

Cantilever Brackets


- Hole Size: 14mm
- Finish: Hot Dip Galvinised

[BACK TO CONTENTS](#)

Braced Cantilever Bracket		
Code	Length	Design Load - UDL
FDGCB320G	320 mm	8.81 kN
FDGCB470G	470 mm	3.43 kN
FDGCB635G	635 mm	3.38 kN
FDGCB780G	780 mm	1.72 kN
FDGCB930G	900 mm	1.47 kN
FDGCB1080G	1080 mm	0.85 kN



Un-Braced Cantilever Bracket		
Code	Length	Design Load - UDL
FDGUBC150G	150 mm	4.85 kN
FDGUBC300G	300 mm	2.35 kN
FDGUBC450G	450 mm	1.60 kN
FDGUBC600G	600 mm	1.25 kN
FDGUBC750G	750 mm	1.05 kN
FDGUBC900G	900 mm	0.75 kN
FDGUBC1000G	1000 mm	0.55 kN




Cantilever Brackets

- Hole Size: 14mm
- Finish: Hot Dip Galvinised

[BACK TO CONTENTS](#)


Back to Back Cantilever Bracket

Code	Length	Design Load - UDL
FDGCB2B305G	305 mm	7.50 kN
FDGCB2B460G	460 mm	5.20 kN
FDGCB2B610G	610 mm	4.10 kN
FDGCB2B760G	760 mm	3.20 kN
FDGCB2B915G	915 mm	2.65 kN



FDG5500G Cantilever Bracket

Code	Length	Design Load - UDL
FDGCBH300G	300 mm	6.95 kN
FDGCBH450G	450 mm	4.80 kN
FDGCBH600G	600 mm	3.60 kN
FDGCBH750G	750 mm	2.90 kN





sales@fdgnc.com

20 Mansel Dr, Warkworth, Auckland 0910 New Zealand

09-275-6811